

Package: drrglm (via r-universe)

September 22, 2026

Title Doubly Regularized Matrix-Variate Regression

Version 0.4.0

Maintainer Zengchao Xu <zengc.xu@aliyun.com>

Description The doubly regularized matrix-variate regression solves a low-rank-plus-sparse structure for matrix-variate generalized linear models through a weighted combination of nuclear-norm and L1-norm. The methodology implemented by this package is described in the paper ``Doubly Regularized Matrix-Variate Regression". See Xu, Luo and Jiang <doi:10.1080/10618600.2026.2702534>.

Depends R (>= 4.3.0)

Imports data.table, glmnet, Rcpp, stats

LinkingTo Rcpp, RcppArmadillo

URL <https://github.com/paradoxical-rhapsody/drrglm>

BugReports <https://github.com/paradoxical-rhapsody/drrglm/issues>

License AGPL-3

Encoding UTF-8

Roxygen list(load=``source", markdown = TRUE)

RoxygenNote 8.0.0

LazyData true

LazyDataCompression xz

Repository <https://paradoxical-rhapsody.r-universe.dev>

Date/Publication 2026-09-22 08:23:26 UTC

RemoteUrl <https://github.com/paradoxical-rhapsody/drrglm>

RemoteRef HEAD

RemoteSha f81c67be907d469cb207516720d6effa34220100

Contents

drr	2
EEG	3
ini_paras	4
simu_factor_model_paras	5
simu_reg_coefs	6
simu_zhouandli2014	7
tune.drrglm	8
tune_drr_factor_model	9
Index	11

drr	<i>Doubly Regularized Matrix-Variate GLMs</i>
-----	---

Description

Solve the following problem

$$\min_{L,S} \left\{ \frac{1}{N} \sum_{n=1}^N \ell(y_n, X_n) + \lambda_1 \|L\|_* + \lambda_2 \|S\|_1 \right\},$$

where $\ell(y_n, X_n)$ refers to the negative-log-likelihood on (y_n, X_n) under pre-specified GLM.

In linear model, the problem has the form

$$\min_{L,S} \left\{ \frac{1}{2N} \sum_{n=1}^N (y_n - \text{tr}(X_n' C))^2 + \lambda_1 \|L\|_* + \lambda_2 \|S\|_1 \right\}, \text{ s.t. } C = L + S.$$

Usage

```
drrglm(
  x,
  y,
  family,
  lambda1,
  lambda2,
  C0 = NULL,
  tol = 0.001,
  maxIter = 300,
  verbose = FALSE
)
```

Arguments

<code>x</code>	$p_1 \times p_2 \times N$ numeric array with mean zero .
<code>y</code>	Numeric vector of length N .
<code>family</code>	See glm and family .
<code>lambda1</code>	λ_1 .
<code>lambda2</code>	λ_2 .
<code>c0</code>	Initialization to C .
<code>tol</code>	Convergence tolerance.
<code>maxIter</code>	Maximal step of iterations.
<code>verbose</code>	Print iterations?

Value

`list(L, S, Lsv, iter, lambda1, lambda2, isConvergent).`

Examples

```
set.seed(2025)
r0 <- 13
c0 <- 17
N <- 500
x <- array(runif(r0*c0*N), c(r0, c0, N))
y <- rnorm(N)

family <- "gaussian"
lambda1 <- 0.15
lambda2 <- 0.04

system.time( egg <- drrglm(x, y, family, lambda1, lambda2) )
```

 EEG

ElectroEncephaloGraphy Data

Description

This data arises from a large study to examine EEG correlates of genetic predisposition to alcoholism. See details.

Usage

```
EEG
```

Format

```
list(alcoholic, control).
```

Details

The original data are fully open-access and available in UCI Machine Learning Repository (<http://kdd.ics.uci.edu/databases/eeg/>). It includes two groups of subjects: 77 alcoholic and 45 control. In the original study, each subject was exposed to either a single stimulus (S1) or two stimuli (S1 and S2), which were pictures chosen from the 1980 Snodgrass and Vanderwart picture set. Each subject underwent 120 trials under each condition.

Here we provide this preprocessed data of the averages of 120 trials under S1 condition, which has been studied in several literature. The dataset is structured as a list containing two arrays,

- EEG\$alcoholic: Array of dimensions 256 x 64 x 77.
- EEG\$control: Array of dimensions 256 x 64 x 45.

References

If you use this dataset, we would be very grateful if you could cite both the original data source and our work:

Zengchao Xu, Shan Luo, and Binyan Jiang. "Doubly Regularized Matrix-Variate Regression". *Submitted*.

Examples

```
data(EEG, package="drrglm")
```

ini_paras

Initialize Parameters

Description

Initialize $\hat{L}$ via nuclear-norm regularized regression.

Usage

```
ini_paras(
  x,
  y,
  family,
  maxRank = min(floor(NROW(x)/2), floor(NCOL(x)/2)),
  tol = 0.001,
  verbose = FALSE
)
```

Arguments

x	Numeric array.
y	Numeric vector.
family	See glm and family .
maxRank	The maximum of rank to be detected.
tol	Convergence tolerance.
verbose	Print iterations?

Value

`list( family, grad, lipschitz, sigma0, rankStar, rankStarHat, lambda.star, L0.star )`

`simu_factor_model_paras`

Simulation: Factor Model with Correlated Noise

Description

$y = Bu + w$ with $u \sim N(0, I_r)$, $w \sim N(0, S)$ and $B \in \mathbb{R}^{p \times r}$.

- `simu_factor_model_paras`: simulate (B, S) .
- `simu_factor_model_data`: simulate y .

Usage

`simu_factor_model_paras(p, r, noise, seed = 2023)`

`simu_factor_model_data(N, B, S)`

Arguments

p	Dimension of data.
r	Number of factors.
noise	Mode of S : • <code>diag</code>: Diagonal matrix. • <code>rand</code>: Nonzero elements at random positions. • <code>tridiag</code>: Tri-diagonal matrix. • <code>block</code>: Block matrix.
seed	Random seed.
N	Sample size.
B	Matrix $p \times r$.
S	Symmetric matrix $p \times p$.

Value

- `simu_factor_model_paras`: `list(B, S)`.
- `simu_factor_model_data`: Numeric matrix y of $N \times p$.

Examples

```
set.seed(2025)
N <- 50
p <- 15
r <- 7

paras <- simu_factor_model_paras(p, r, 'diag')
paras <- simu_factor_model_paras(p, r, 'rand')
paras <- simu_factor_model_paras(p, r, 'tridiag')
paras <- simu_factor_model_paras(p, r, 'block')

DT <- simu_factor_model_data(N, paras[["B"]], paras[["S"]])
```

simu_reg_coefs	<i>Simulation: Matrix-Variate GLM</i>
----------------	---------------------------------------

Description

Simulation: Matrix-Variate GLM

Usage

```
simu_reg_coefs(p1, p2, rank0, S.type, seed = 2023)

simu_reg_data(family, N, C0, err.student.dof = NULL)
```

Arguments

p1	Row dimension.
p2	Column dimension.
rank0	Rank of L.
S.type	Type of S. • zero: Zero matrix. • rand: Nonzero elements at random positions. • block: Block matrix. • diag: Diagonal matrix.
seed	Random seed.
family	See glm and family .
N	Sample size.

`C0` Coefficient matrix.

`err.student.dof`

The degree of freedom of Student-*t* for error term in family="gaussian". By default it is NULL, corresponding to normal error.

Value

- `simu_reg_coefs`: list(L, S).
- `simu_reg_data`: list(train=list(x, y), test=list(x, y)).

Examples

```
p1 <- 10
p2 <- 9
rank0 <- 3

coefs <- simu_reg_coefs(p1, p2, rank0, "zero")
coefs <- simu_reg_coefs(p1, p2, rank0, "rand")
coefs <- simu_reg_coefs(p1, p2, rank0, "block")
coefs <- simu_reg_coefs(p1, p2, rank0, "diag")

N <- 100
S.type <- "rand"
family <- "binomial"

coefs <- simu_reg_coefs(p1, p2, rank0, S.type)
C0 <- coefs[["L"]] + coefs[["S"]]

set.seed(2025)
DT <- simu_reg_data(family, N, C0)
DT <- simu_reg_data("gaussian", N, C0, err.student.dof=3)
```

simu_zhouandli2014 *Simulation: Setups in Regularized Matrix Regression*

Description

Simulation: Setups in Regularized Matrix Regression

Usage

```
simu_zhouandli2014(N, p1, p2, r0, s0, family)
```

Arguments

N	Sample size.
p1	Row dimension.
p2	Column dimension.
r0	Rank.
s0	signal proportion.
family	"gaussian" or "binomial".

Value

```
list( C0, train=list(x, y), test=list(x, y) ).
```

References

Zhou Hua and Li Lexin (2014). Regularized Matrix Regression. Journal of the Royal Statistical Society (Series B). doi:[10.1111/rssb.12031](https://doi.org/10.1111/rssb.12031)

Examples

```
N <- 100
p1 <- 64
p2 <- 64
r0 <- 1
s0 <- 0.05
family <- 'gaussian'

set.seed(2026)
DT <- simu_zhouandli2014(N, p1, p2, r0, s0, family)
```

tune.drrglm

Doubly Regularized Regression for Matrix-Variate Data

Description

Tune the (λ_1, λ_2) in [drr](#).

Usage

```
tune_drrglm(
  iniParas,
  x,
  y,
  lambda1.factor = 1.3^seq(-3, 3, 0.2),
  maxCard = 30,
  tol = 0.001,
  maxIter = 500
)
```

Arguments

iniParas	Initial values returned by ini_paras . See examples below.
x	Numeric array.
y	Numeric vector.
lambda1.factor	Factor on initial guess λ_1^* (By default $1.3^{\text{seq}(-3, 3, 0.2)}$).
maxCard	The maximal cardinality of S .
tol	Convergence tolerance.
maxIter	Maximal step of iterations.

Value

List.

Examples

```
p1 <- 10
p2 <- 9
rank0 <- 3
S.type <- "rand"
coefs <- simu_reg_coefs(p1, p2, rank0, S.type)

N <- 500
family <- "gaussian"
L0 <- coefs[["L"]]
S0 <- coefs[["S"]]
C0 <- L0 + S0
DT <- simu_reg_data(family, N, C0)

x <- DT[["train"]][["x"]]
y <- DT[["train"]][["y"]]

lambda1.factor <- 1.1^(0:1)
maxRank <- 5

system.time( iniParas <- ini_paras(x, y, family, maxRank) )
system.time( drrObj <- tune_drrglm(iniParas, x, y, lambda1.factor) )
```

tune_drr_factor_model *Simulating Data for Factor Model with Correlated Noise*

Description

Doubly regularized decomposition for covariance matrix in factor model.

Usage

```
tune_drr_factor_model(  
  y,  
  lambda1.factor = 1.1^(-2:2),  
  S.diag.penalize = FALSE,  
  tol = 0.001,  
  maxIter = 500  
)
```

Arguments

y	Numeric matrix of $N \times p$.
lambda1.factor	Factor on λ_1^* (by default $1.1^{(-2:2)}$).
S.diag.penalize	Whether to penalize the diagonal elements of S (by default FALSE).
tol	Convergence tolerance.
maxIter	Maximal step of iterations.

Value

List.

Examples

```
set.seed(2025)  
N <- 500  
p <- 30  
r <- 10  
noise <- "diag"  
paras <- simu_factor_model_paras(p, r, noise)  
y <- simu_factor_model_data(N, paras[["B"]], paras[["S"]])  
lambda1.factor <- 1.1^(-1:1)  
system.time( egg <- tune_drr_factor_model(y, lambda1.factor) )
```

Index

* datasets

EEG, [3](#)

drr, [2](#), [8](#)

drrglm(drr), [2](#)

EEG, [3](#)

family, [3](#), [5](#), [6](#)

glm, [3](#), [5](#), [6](#)

ini_paras, [4](#), [9](#)

simu-factor-model

(simu_factor_model_paras), [5](#)

simu-reg-model(simu_reg_coefs), [6](#)

simu_factor_model_data

(simu_factor_model_paras), [5](#)

simu_factor_model_paras, [5](#)

simu_reg_coefs, [6](#)

simu_reg_data(simu_reg_coefs), [6](#)

simu_zhouandli2014, [7](#)

tune.drrglm, [8](#)

tune_drr_factor_model, [9](#)

tune_drrglm(tune.drrglm), [8](#)